

DEVELOPMENT SERVICES (Edmonton Tower) 2nd Floor, 10111 – 104 Avenue NW EDMONTON, AB T5J 0J4

PHONE: 311 or if outside of Edmonton 780-442-5311 EMAIL: developmentservices@edmonton.ca

Garden Suite Housing Application

		Office Use O	Inly
SECTION 1 – PERMIT INFORMATION		CITY Proje	ect #
Project Address: (Provide at least one of the	ne following) — Please note:	: it can not be an interse	ection
PROJECT ADDRESS (MUNICIPAL):			
LEGAL DESCRIPTION PLAN:	BLOCK:		LOT:
Has a Garden Suite existed on this lot previously			
If yes, what year was the Garden Suite built?	Existing Suite For defin		
Is this application for a: New Garden Suite	_		
Applicant Information:	CITY Customer	' ID # (if known)	
APPLICANT / CONTACT:			
As the applicant I affirm:	atad proporty		
I am the registered owner of the above nI have entered into a binding agreement		ronerty with the registers	ed owner(s)
☐ I have permission of the registered owne			
•	ion is complete, and any notice r(s) of the above noted proper	es identifying any outstan	t limited to development permit decisions, ding documents and information, by email pplication for a Combination Permit, which
BUSINESS NAME (IF APPLICABLE):			
MAILING ADDRESS:		CITY:	
PROVINCE:	POSTAL CODE:		
EMAIL:	INSPECTION RESULTS TO BE M	MAILED TO THIS EMAIL? YES	□ NO □
PHONE #:	FAX #:	CELL #: _	
Signature :		Date:	
Description of Work: (in addition to the gar	den suite dwelling check appli	icable proposed construc	tion)
☐ Attached carport ☐ Covered deck ☐ Unco	overed deck 🗆 Veranda 🗅 F	Fireplace □ Balcony □	Exterior hot tub
☐ Demolition of existing garden suite ☐ So	lar photovoltaic system 🗖 S	Solar thermal system 🗖	Geoexchange system
□ Other:		·	- ,
Please complete Sections 2&3 on th	e following pages.		
For Office Use Only:			
Permit Required? Yes 🗖 No 🗖 Creat	e Sub-job from Project No.		
New Sanitary Sewer Trunk Charge Required?	? Yes □ \$	No ☐ Lot Gradin	g Required? Yes ☐ No ☐
Zoning: Overlay:			
This project is: Discretionary Use Perr			
Development Permit Description:			
Paviawad Ry: (Print Nama)			Date:



Applicable fees

DEVELOPMENT SERVICES (Edmonton Tower) 2nd Floor, 10111 – 104 Avenue NW EDMONTON, AB T5J 0J4

PHONE: 311 or if outside of Edmonton 780-442-5311 EMAIL: developmentservices@edmonton.ca

SECTION 2 - RITH DING PERMIT INFORMATION

SE	<u>CTION 2 – BUILDING PERMI</u>	T INFORMATION	CITY Project #
1) #	of new gas meters?		
	What is the construction value for the (The construction value is the value of all rough the demolition)	e garden suite? \$_ naterials and labour (excluding Prof	ressional fees) to do the project. For demolitions, the construction value is the total cost
3) S	quare Footage for the garden suite?	sq ft.	
4) S	Subcontractor List		
Sı	ubcontractors	City Customer ID #	Business Name & Address
Вι	uilding (if different from applicant)		
Не	eating & Ventilation		
PI	umbing & Gas		
Se	ewer		
Ele	ectrical – Wiring		
Ele	ectrical – Underground		
Te	emporary Gas Heat		
per	mit issuance.		Protection Act to have a compliant warranty or proof of exemption prior to OR, Exemption? Yes Copy Attached
	ending, sign to confirm warranty (or		
Sign	nature:		Date:
	CTION 3 — DEVELOPMENT/E e (1) complete set of drawings that inc		MISSION REQUIREMENTS: See page 3 for additional information
One	e (1) complete set of drawings that inc	ciade the following. (Millimum's	icale. Metric 1:100 / Imperial 1/8)
CHE	CK OFF INFORMATION SUBMITTED WITH	THIS APPLICATION **In	ncomplete submissions can not be processed**
	Plot plan or site plan with grade elev	ations (at the four corners of si	te) and main floor geodetic elevation
	Signed Construction Site Manageme	ent Acknowledgement Form (Re	quired for Mature and Established Neighbourhoods)
	Floor and elevation plans (include a	basement floor plan if also appl	ying for a basement development)
	Cross sections and specifications de	tails	
	Foundation plans/beams / columns/	column loading / pad details /	type of concrete to be used
	Grade beam and/or pile foundation	details for attached garage, ver	anda, covered deck, etc.
	Foundation lateral support details (i	nclude site-specific engineered	foundation / window / stairwell bracing or reinforcing details)
		· · · · · · · · · · · · · · · · · · ·	ayout (include bearing details & load transfer points)
	Engineered floor joist/truss and eng		
	•		(engineer stamped drawings / details)
		7 sq. meters –the "Abandoned	Wells Confirmation Form – Proposed Development" form and a printout of the

Personal Information required by City of Edmonton application forms is collected under authority of sections 33(a) and (c) of the Alberta Freedom of Information and Protection of Privacy (FOIP) Act. Your personal information will be used to process your application(s). Please be advised that your name, address and details related to your permit may be included on reports that are available to the public as required or allowed by legislation. If you have any questions, please contact a Service Advisor at the Edmonton Service Centre at 780-442-5054.

Page 2 of 6 Apr, 2018



Flush connections for built up beams

DEVELOPMENT SERVICES (Edmonton Tower) 2nd Floor, 10111 – 104 Avenue NW EDMONTON, AB T5J 0J4

PHONE: 311 or if outside of Edmonton 780-442-5311 EMAIL: developmentservices@edmonton.ca

To minimize delays in processing your application, the application form must be completed and accompanied by the required plans/information for your project. Additional information may be required as considered necessary, to demonstrate compliance with applicable Edmonton Bylaws and Alberta Building Code, to enable the permit to be issued. Incomplete submissions can not be processed. **NOTE: Faxed or Emailed applications will not be accepted.**

<u>Plo</u>	t Plan or Site Plan to show the following		
	North arrow, scale and date of preparation		
	Municipal address and legal description		
	Dimensions of the site (property lines)		
	Dimensions and location of all proposed and existing structur	es in	cluding cantilevers and overhangs and distances to property
_	lines	:4-	
	Dimensions/location of existing and proposed accesses to the Elevations of finished grades, bottom of footings, top of foun		
	Elevations of finished grades, bottom of footings, top of four	uatic	on wan, mished main noor
Flo	or Plans to show the following – minimum scale- metric 1:100	impe	erial 1/8"
	Dimensions of the proposed structure		
	All levels and square footage of each level		
	Dimensions and layout, location of walls; doors; and windows	s (inc	clude sizes) and use of all rooms/areas
<u>Bui</u>	lding Elevations and Sections to show the following		
	All sides of the house		
	Building height (m) - from the top of the finished floor to mid	-poir	nt of the roof <u>AND</u> from the top of the finished floor to the top o
	roof (ridge)		
	Finished ground level		
	Exterior finishing materials		
	Materials and assemblies of materials forming floors, walls, re	oofs,	decks etc.
Ma	nufactured structural component information required to be s	ubm	aitted (see Standata 06-BCI-015)
	Supplier letters for roof trusses, floor joists, and/or structura	al bea	ams & columns
	Layouts for:		
	a) Roof		
	b) Floor joists of simple or continuous spans		
	Note: Where continuous spans are incorporated into the reactions and all construction details that are covered in		sign, the layout schematic should also show all joist and/or beam manufacturer's product guide
	Manufacturer's design drawings for all manufactured structu	ral c	omponents not covered by (a) or (b) above
			nrough uniform loading covered by ABC 2014-Division B-Part9.
	Design of engineered columns where loads exceed 8000 lbs, i		
<u>As</u> p	pects of building that may require professional or engineer invo	olven	nent (stamped design/engineer letter etc.)
	Foundation construction act in Code (DMF ICF atc.)		Fotogram and the Code had about the
	Foundation construction not in Code (PWF, ICF, etc.)		Exterior walls exceeding Code height limits
	Foundation design where geotechnical information indicates it is required		Dimension lumber joists exceeding Code table limits Cantilevered joists not in Code
	Foundation lateral bracing for wall length, height or backfill		Masonry supported on wood frame
_	condition		Concrete topping on wood floor system
	Grade beams & piles not per Standata 90-DR-092		Construction with uncommon housing materials (steel,
	Structural concrete (slabs, brackets, etc)	_	precast concrete, straw bale, SIP, ICF, etc.)
	Retaining walls connected to building or required for		Installation of renewable energy devices (solar collectors etc)
_	building integrity	_	Exterior cladding systems not in Code
	Complex roof or floor (stick framed or engineered)		Hydronic heating systems

Page 3 of 6 Apr, 2018

□ Spray foam products and installation



DEVELOPMENT SERVICES (Edmonton Tower) 2nd Floor, 10111 – 104 Avenue NW EDMONTON, AB T5J 0J4

PHONE: 311 or if outside of Edmonton 780-442-5311 EMAIL: developmentservices@edmonton.ca

Abandoned Wells Confirmation Form - Alberta Government's Energy Resources Conservation Board (ERCB) Directive -079

□ For structures over 47 sq meters –"Abandoned Wells Confirmation Form – Proposed Development" form and a printout of the map that was used to confirm the absence/presence of abandoned wells must be submitted.

Solar Panels -

☐ If construction involves solar panels (Thermal or PhotoVoltaic) — Applicant must see Solar Energy Systems brochure for additional submission requirements.

Geoexchange System -

☐ If construction involves Geoexchange System – Applicant must see Geoexchange system installation application for additional submission requirements. (www.edmonton.ca/currentplanningforms)

Temporary Heat -

□ Temporary gas heat

Payment of Fees

applicable fees

Permit fees must be paid in full at the time of application.

We accept cash, debit, cheque or credit card. If applying, other than in person, a service representative will call you to advise you of your fees. Please note that the City of Edmonton, in accordance with Payment Card Industry, has taken measures to protect your payment card information. We are required to delete applications submitted with credit card information by unsecured methods such as Fax or e-mail.

Office hours are Monday to Friday, 8:00 am to 4:30 pm. The office is closed on statutory holidays

Definitions from Edmonton Zoning Bylaw 12800 -

Garden Suite:

An Accessory building containing a Dwelling, which is located separate from the principal Use which is Single Detached Housing, and which may contain a Parking Area. A Garden Suite has cooking facilities which are separate from those of the principal Dwelling located on the site. This Use Class does not include Secondary Suites, Blatchford Lane Suites, or Blatchford Accessory Suites.

Page 4 of 6 Apr, 2018

Abandoned Wells Confirmation Form - Proposed Development

Note: This form is to be signed by the applicant at the time of Development Permit application, and to be submitted with a printout of the map(s) that was used to confirm the absence/presence of abandoned well(s).

<u>If abandoned</u>	<u>d wells are</u>	absent wit	<u>thin the site o</u>	f propo	osed development:	
		as set out in	ERCB Directive 07	79, Surfa	formation provided by th sce Development in Proxing y abandoned wells withing	nity to Abandoned
Printe	d Name			Signa	ture	
Compa	any affiliation o	of the signer		Date		
I,	Board ("ERCE n advise that has been con with ERCB D ndoned wells	3") as set out i the licensee(s tacted in orde irective 079. T s prior to cons	, have re n ERCB Directive) responsible for er to have the <i>Ab</i> To prevent damag	eviewed 079, Sur all aband andoned ge to the	proposed developm information provided by face Development in Providenced wells within the sit if Well Locating and Testing well, a temporary identification of the confirmed well location in the confirmed well locatio	the Energy Resources ximity to Abandoned te of proposed ing Protocol completed fication marker will be
ERCB Well License	# Lice	nsee name	Licensed Surface (e.g., 04-20-052-2		Contact personnel name	Phone number
Printe	d Name			Signa	ture	
Compa	any affiliation o	of the signer		Date		
Munic	ipal Address:					
Legal	Description:	Lot:	Block:		Plan:	
Ci	ty File #:			LDA:		

Page 5 of 6 Apr, 2018

Why do I need to disclose information about abandoned wells on my parcel?

New Requirements

Effective November 1, 2012 the Subdivision and Development Regulation (Alberta Regulation 160/2012) has changed. The changes relate to the Subdivision and Development requirements around abandoned well sites. The new provisions require some changes to our business practices. In addition to our current application submission requirements, all new Development Permit and Subdivision Applications must include the following:

Development Permit Application

An application for a development permit for a new building that will be larger than 47 square meters, or an addition to or an alteration of an existing building that will result in the building being larger than 47 square meters, must include:

- Information provided by the Energy Resources Conservation Board (ERCB) identifying the location or confirming the absence of any abandoned wells within the parcel on which the building is to be constructed, or, in the case of an addition, presently exists.
- This information can be obtained by either contacting the Energy Resources Customer
 Care Centre at 1-855-297-8311 (toll free) or using the GeoDiscover Alberta Map at:
 www.geodiscoveralberta.ca
 to confirm whether an abandoned well is located on your
 property.
 - If you do not have an abandoned well site on your property, you must fill out the "Abandoned Wells Confirmation Form – Proposed Development" and provide a copy of the map that was used to confirm the absence of abandoned wells on your property. This information must be included with your development application.
 - If you do have an abandoned well on your property, you must first meet the
 requirements as set out in ERCB's Directive 079 before you can apply for a permit. Once
 ERCB's Directive 079 requirements have been met, you must fill out the "Abandoned
 Wells Confirmation Form Proposed Development" and include a copy of the map used
 to confirm well location(s) with your development application.

The information is not required if it was submitted to the same development authority within the last year.

The following links provide further information on the added provisions.

Information Bulletin, Alberta Municipal Affairs -

http://www.municipalaffairs.alberta.ca/documents/msb/Information Bulletin 05 12.pdf

ERCB Directive-

http://www.ercb.ca/directives/Directive079.pdf

Page 6 of 6 Apr, 2018

ABC2014:B:9.36. ENERGY EFFICIENCY

APPLICATION CHECKLIST



PROJECT ADDRESS:		
□ PRESCRIPTIVE PATH	□ PRESCRIPTIVE WITH	□ PERFORMANCE PATH
Complete (1)A –OR– (1)B and (2) to (5)	TRADE-OFF PATH	Complete (5) only below, and attach

below Complete (1)A -OR- (1)B and (2) to (5) below, and attach Trade-off Calculator results

Complete (5) only below, and attach Performance Report and mandatory Edmonton Summary form

$\begin{tabular}{ll} \textbf{1a} \\ \textbf{Effective thermal resistance of assemblies in buildings WITHOUT heat-recovery ventilator} \\ (HRV) 9.36.2.6.A \& 9.36.2.8.A \\ \end{tabular}$

ASSEMBLY LOCATION	MINIMUN (m2K/W		-			PROPOSED ASSEMBLY including insulation type/R-value
ROOF						
Cathedral ceilings and flat roofs	5.02	□ N	I/A	equal or better	☐ less	
Ceilings under attic, including over attached garages	10.43	□ N	I/A	☐ equal or better	less	
ABOVE-GROUND WALLS			•			
Exterior wall	3.08	□ N	I/A	□ equal or better	☐ less	
Tall walls	3.08	□ N	I/A	□ equal or better	☐ less	
House-to-attached garage walls	2.92	□ N	I/A	□ equal or better	☐ less	
Other: kitchen cabinet wall(s)	3.08	□ N	I/A	□ equal or better	☐ less	
OTHER:	3.08	□ N	I/A	□ equal or better	☐ less	
RIM JOISTS						
Parallel to joists, or pony wall	3.08	□ N	I/A	□ equal or better	☐ less	
Perpendicular to joists	3.08	□ N	I/A	□ equal or better	☐ less	
ABOVE-GROUND FLOOR						
Exterior cantilever	5.02		I/A	equal or better	less	
Over attached garage	4.86		I/A	equal or better	less	

ASSEMBLY LOCATION	MINIMUM "ETR" (m2 K/W) (RSI)				PROPOSED ASSEMBLY including insulation type/R-value
BELOW-GRADE WALLS					
Frostwalls, above–ground wall portions where average exposure < 0.6m	3.46	□ N/A	equal or better	less	
Foundation-level above-ground wall portions where average exposure ≥ 0.6 m	3.08	□ N/A	☐ equal or better	less	
UNHEATED FLOOR Above frost line	1.96	□ N/A	☐ equal or better	less	
ANY HEATED FLOOR In ground contact	2.84	□ N/A	equal or better	less	
SLAB ON GRADE with integral footing	3.72	□ N/A	a equal or better	less	

1bEffective thermal resistance of assemblies in buildings WITH heat-recovery ventilator – (HRV) 9.36.2.6.B & 9.36.2.8.B

ASSEMBLY LOCATION	MINIMUN	и "ETR"			PROPOSED ASSEMBLY
	(m2 K/W	/) (RSI)			including insulation type/R-value
ROOF					
Cathedral ceilings and flat roofs	5.02	□ N/A	equal or better	☐ less	
Ceilings under attic, including over attached garages	8.67	□ N/A	□ equal or better	☐ less	
ABOVE-GROUND WALLS					
Exterior wall	2.97	□ N/A	☐ equal or better	☐ less	
Tall walls	2.97	□ _{N/A}	equal or better	□ _{less}	
House-to-attached garage walls	2.81	□ N/A	☐ equal or better	□ less	
Other: kitchen cabinet wall(s)	2.97	□ N/A	☐ equal or better	☐ less	
OTHER:	2.97	□ N/A	☐ equal or better	☐ less	
RIM JOISTS					
Parallel to joists, or pony wall	2.97	□ N/A	☐ equal or better	☐ less	
Perpendicular to joists	2.97	□ N/A	☐ equal or better	☐ less	
ABOVE-GROUND FLOOR			,		
Exterior cantilever	5.02	□ N/A	☐ equal or better	☐ less	
Over attached garage	4.86	□ N/A	☐ equal or better	☐ less	
BELOW-GRADE WALLS			1		
Frostwalls, above–ground wall portions where average exposure < 0.6m	2.98	□ N/A	□ equal or better	□ less	
Foundation–level above–ground wall portions where average exposure $\geq 0.6 \text{m}$	2.97	□ N/A	□ equal or better	☐ less	
UNHEATED FLOOR above frost line	1.96	□ N/A	□ equal or better	☐ less	
ANY HEATED FLOOR In ground contact	2.84	□ N/A	□ equal or better	less	
SLAB on GRADE	2.84	□ N/A	☐ equal or better	☐ less	

2Check proposed windows, doors, etc; maximum prescriptive overall thermal transmittance "u-values"

FENESTRATION & DOOR COMPONENTS	MAXIMU	M "U" value	(W/m2 K)	
Windows (max USI)	1.60	□ N/A	equal or higher performing	9.36.2.7.A alternative: min ER=25
Exterior doors (max USI)	1.60	□ N/A	equal or higher performing	9.36.2.7.A
Single exterior door exception (max USI)	1.60	□ N/A	equal or higher performing	9.36.2.7.(5), NOTE on plans
Glass block; max area: 1.85 m2 (max USI)	1.60	□ N/A	equal or higher performing	9.36.2.7.(4), NOTE on plans
Skylights (max USI)	1.60	□ N/A	equal or lower performing	9.36.2.6.(4), include shaft ETR/detail
Attic/access hatches (min nom RSI = 2.6)	1.60	□ N/A	equal or lower performing	9.36.2.7.(8), NOTE on plans
Garage overhead doors (min nom RSI = 1.1)	1.60	□ N/A	equal or higher performing	9.36.2.7.(7), NOTE on plans

3 CHECK HVAC components/capacity/standard/minimum performance; or write 9.36.3.10. selection(s) in space below

COMPONENT/EQUIPMENT	HEATING/COOLING CAPACITY	STANDARD	MIN PERFORMAI	NCE
Gas-fired forced air furnace	< 65.9kW [222,000Btu/h]	CAN/CSA-P.2	≥ AFUE 92%	☐ YES
Gas-fired boiler	≤ 88kW[300kBtu/h]	CAN/CSA-P.2	≥ AFUE 90%	☐ YES
Electric tank	≤ 73.2kW if SWH-based	CAN/CSA-P.9	TPF = 0.65	□ YES
Electric tankless	≤ 87.9kW if boiler-based	CAIN/ CSA-1.9	171 - 0.05	☐ 1F2
Other:				☐ YES

4CHECK Service Water Heating components/input/standard/performance; or write 9.36.4.2. selection in space below

	HEATING/COOLING CAPACITY	STANDARD	MIN PERFORMA	NCE
Gas-fired hot water tank	< < 22kW [75,000Btu/h]	CAN/CSA-P.2	≥ AFUE 92%	☐ YES
Can Evaluation	> 73.2kW [250,000Btu/h]	CSA 4.3 etc	Et ≥ 80%	□ VEC
Gas-fired tankless	≤ 73.2kW [250,000Btu/h]	CAN/CSA-P.7	EF ≥ F0.8	YES
Electric tank	≤ 50-270L [13-71usg]	CAN/CSA-C191	$SL \le 35 + 0.20V$ (top) $SL \le 40 + 0.20V$ (bottom)	□ YES
Electric tankless	-	_	approaching 100%	☐ YES
Other:				☐ YES

5 INDICATE the following, as applicable

PRIMARY WALL AIR BARRIER LOCATION/MATERIAL: PRIMARY CEILING BELOW ATTIC/VAULT/	FLAT				
Interior poly with spray foam at rim joists and cantilevers					
Interior poly with exterior flexible wrap at rim joists and cantilevers Interior poly					
Interior poly with sealants/tapes at floor, window, wall and ceiling intersections Other: (specify)		_ 🗆			
Exterior flexible air barrier system with all joints and edges sealed					
Exterior rigid air barrier system with all joints and edges sealed					
Other: (specify)					
Intake duct has "fail-open" motorized damper—except where disallowed by other regulation or where system					
operates continuously? [9.36.3.3.]					
Discharge duct has motorized damper, or gravity/spring-operated backflow damper installed? [9.36.3.3.]					
Min 12mm thick pipe insulation for minimum 2m from inlet and outlet of water heater?					
Min 12mm thick pipe insulation for all piping on recirculating service hot water system 9.36.4.4 (1)					
HRV conforms CAN/CSA-C439 "Rating the Performance of Heat/Energy-Recovery Ventilators" sensible HR					
efficiency ≥60%@0°C and ≥55%@-25°C?					
A Blower Door Test Report will be submitted after construction and prior to occupancy inspection for energy code compliance					